



Safety Data Sheet

Adhesive mixture for Ecotrap and Refill Board

Safety Data Sheet dated 4/10/2022, version 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: Adhesive mixture for ecotrap rats/ecotrap rats plus/ecotrap quadro/quadro box/refill boards mice and rats/book refill/adhesive for fruit trees and customized products
Trade code: P-02004, P-02004B, P-02004G40, P-02004G40B, P-02104DIN, P-02004CIN, P-02013B, P-02048A, P-02148DIN, P-02031, P-02041, P-02005, P-02019, P-02053, P-02054, P-02055 and customized codes.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Adhesive mixture for the production of adhesive traps for mice and rats and traps for fruit trees.

Product category

PC1 Adhesives, sealants

Uses advised against:

the mixture has to be used for the mentioned application and use.

1.3. Details of the supplier of the safety data sheet

Company:

GEA SRL

Via A. B. Sabin, 31

20019 - Settimo Milanese (MI) - ITALIA

Tel: +39 02 33514890

Fax: +39 02 00665233

Competent person responsible for the safety data sheet:

msds@geaitaly.it

1.4. Emergency telephone number

UK Emergency numbers: 999 or 112

Company emergency telephone number: +39 02 33514890 (available from Monday to Friday from 9 a.m. to 6 p.m., for technical assistance only).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Hazard pictograms:

None

Hazard statements:

None

Precautionary statements:

None

Special Provisions:

None

Special provisions according to Annex XVII of REACH and subsequent amendments:



Safety Data Sheet

Adhesive mixture for Ecotrap and Refill Board

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
$\geq 0.1\%$	cyclohexane	Index number: 601-017-00-1	2.6/2 Flam. Liq. 2 H225
$< 0.25\%$		CAS: 110-82-7	3.10/1 Asp. Tox. 1 H304
		EC: 203-806-2	3.2/2 Skin Irrit. 2 H315
		REACH No.: 01-2119463273-41	3.8/3 STOT SE 3 H336
			4.1/A1 Aquatic Acute 1 H400
			4.1/C1 Aquatic Chronic 1 H410

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide

foam

powder

Water haze



Safety Data Sheet

Adhesive mixture for Ecotrap and Refill Board

Extinguishing media which must not be used for safety reasons:
High pressure water jets.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.
Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.
Remove persons to safety.
See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
See also section 8 for recommended protective equipment.
Advice on general occupational hygiene:
Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos notrabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
EU	OEL EU	Direttiva (UE) 2017/2398; Direttiva (UE) 2017/164; Direttiva 2009/161/UE; Direttiva



Safety Data Sheet

Adhesive mixture for Ecotrap and Refill Board

2006/15/CE; Direttiva
2004/37/CE; Direttiva 2000/39/CE; Direttiva 91/322/CEE.
TLV-ACGIH ACGIH 2019

Cyclohexane – CAS: 110-82-7

Country	Type	Long mg/m3	Long ppm	Duration
DEU	AGW	700	200	8h
DEU	MAK	700	200	8h
ESP	VLA	700	200	8h
FRA	VLEP	700	200	8h
GBR	WEL	350	100	8h
ITA	VLEP	350	100	8h
Country	Type	Long mg/m3	Long ppm	Duration
ITA	TWA	344	100	8h
EU	IOELV	700	200	8h
	TVL-ACGIH	344	100	8h
USA	PEL	1050	300	8h
USA	REL	1050	300	8h
USA	TLV	344	100	8h

DNEL exposure limit values

cyclohexane - CAS: 110-82-7

Industrial worker: 2016 mg/kg - Exposure: Human Skin - Frequency: Long term, systemic effects - Notes: (Rat)

Industrial worker: 1400 mg/m³ - Exposure: Human Inhalation - Frequency: Short term, systemic effects - Notes: (Fish)

Industrial worker: 700 mg/m³ - Exposure: Human Inhalation - Frequency: Long term, local effects

Industrial worker: 700 mg/m³ - Exposure: Human Inhalation - Frequency: Long term, systemic effects

Industrial worker: 1400 mg/m³ - Exposure: Human Inhalation - Frequency: Short term, local effects

PNEC exposure limit values

cyclohexane - CAS: 110-82-7

Target: Fresh water - Value: 0.207 mg/l

Target: Freshwater sediment - Value: 16.68 mg/kg

Target: Seawater - Value: 0.207 mg/l

Target: Sea water sediment - Value: 16.68 mg/l

Target: STP - Value: 3.24 mg/l

Target: Soil - Value: 3.38 mg/kg

Target: Intermittent Release - Value: 0.207 mg/l

8.2. Exposure controls

Eye protection:

Safety glasses.

Protection for skin:

Wear category I professional long-sleeved overalls and safety footwear (ref. Directive Regulation 89/686/EEC and standard EN ISO 20344).

Protection for hands:

Wear protective gloves.

Respiratory protection:

If the limit value of the substance, or of one of the substances in the product, is exceeded (ex. TLV-TWA), we suggest the use of a mask with type A filter, whose class (1,2 or 3) must be chosen according to the use limit concentration (ref. Reg. EN14385). In case of presence of gases or vapours of different nature and/or gases or vapours with particles (aerosol, fumes,



Safety Data Sheet

Adhesive mixture for Ecotrap and Refill Board

fogs, etc.), it is necessary to use combined filters. The use of respiratory protective devices is necessary in case the adopted technical measures are not sufficient to limit the worker exposure to the considered limit values. The mask protection is limited.

For the right choice of the protective respiratory device consider the EN 529 Regulation.

Thermal Hazards:

None

Environmental exposure controls:

Emissions from production processes, including those from ventilation equipment, should be controlled in order to comply with environmental legislation.

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	N.A.	--	--
Odour:	Slight of glue if not flavoured; characteristic in case flavours were used (banana, hazelnut, black cherry, according to technical specifications)	--	--
Melting point/freezing point:	N.A.	--	--
Boiling point or initial boiling point and boiling range:	N.A.	--	--
Flammability:	N.A.	--	--
Lower and upper explosion limit:	N.A.	--	--
Flash point:	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
pH:	N.A.	--	--
Kinematic viscosity:	N.A.	--	--
Solubility in water:	Insoluble	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	N.A.	--	--
Density and/or relative density:	0.83-0.93@ 20°C	--	--
Relative vapour density:	N.A.	--	--



Safety Data Sheet

Adhesive mixture for Ecotrap and Refill Board

Relative density:	0.83-0.93 @ 20°C	--	--
-------------------	------------------	----	----

Particle characteristics:

Particle size:	N.A.	--	--
----------------	------	----	----

9.2. Other information

Properties	Value	Method:	Notes
Explosive properties:	Non explosive	--	--
Viscosity:	>20.5 mm ² /sec (40°C)	--	--
Oxidizing properties:	Non oxidizing	--	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

CYCLOHEXANE: it can react with strong oxidizing agents and liquid nitrogen oxide. It can create explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating and any ignition source.

10.5. Incompatible materials

CYCLOHEXANE: natural and butyl rubber, neoprene, chloride of polyvinyl, polyethylene.

10.6. Hazardous decomposition products

By thermal decomposition or in case of fire, gases and vapours, which are potentially harmful to health, can be released.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

Miscela adesiva per Ecotrap e Tavole Refill

a) Acute toxicity

Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation

Not classified

Based on available data, the classification criteria are not met

c) serious eye damage/irritation

Not classified

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

f) Carcinogenicity

Not classified

Based on available data, the classification criteria are not met



Safety Data Sheet

Adhesive mixture for Ecotrap and Refill Board

- g) Reproductive toxicity
Not classified
Based on available data, the classification criteria are not met
 - h) STOT-single exposure
Not classified
Based on available data, the classification criteria are not met
 - i) STOT-repeated exposure
Not classified
Based on available data, the classification criteria are not met
 - j) aspiration hazard
Not classified
Based on available data, the classification criteria are not met
- Toxicological information of the main substances found in the product:
cyclohexane - CAS: 110-82-7

Information on likely routes of exposure

Workers: inhalation; skin contact.

Population: ingestion of contaminated food or water; inhalation of air; skin contact with products containing the substance.

Immediate, delayed and chronic effects from short- and long-term exposure

It is irritant for skin and mucous membranes; the neurolesive action can occur with elevated doses and it is due to Cyclohexanone, its metabolite.

Interactive effects

It can enhance the effects of tri-ortho-cresyl phosphate (TOCP).

a) Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Notes: Metodo equivalente o similare a OECD Guideline 401.

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg - Notes: Metodo equivalente o similare a OECD Guideline 402.

Test: LC50 - Route: Inhalation - Species: Rat > 5540 ppm - Duration: 4H - Notes: Metodo equivalente o similare a OECD Guideline 403.

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Miscela adesiva per Ecotrap e Tavole Refill

Not classified for environmental hazards

Based on available data, the classification criteria are not met

cyclohexane - CAS: 110-82-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 4.53 mg/l - Duration h: 96 - Notes: Pimephales promelas. Metodo equivalente o similare a OECD Guideline 203.

Endpoint: EC50 - Species: Crustaceans = 0.9 mg/l - Duration h: 48 - Notes: Daphnia magna. Metodo equivalente o similare a OECD Guideline 202.

Endpoint: EC50 - Species: Algae = 3.4 mg/l - Duration h: 72 - Notes:

Pseudokircheneriella subcapitata. Metodo equivalente o similare a OECD Guideline 201.



Safety Data Sheet

Adhesive mixture for Ecotrap and Refill Board

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 0.9 mg/l - Duration h: 72 - Notes:

Pseudokircheneriella subcapitata. Metodo equivalente o similare a OECD Guideline 201.

12.2. Persistence and degradability

Miscela adesiva per Ecotrap e Tavole Refill

Biodegradability: Readily biodegradable - Duration h: 28 days - %: 77 - Notes: (OECD Guideline 301 F).

cyclohexane - CAS: 110-82-7

Biodegradability: Readily biodegradable - Duration h: 28 days - %: 77 - Notes: % (OECD Guideline 301 F).

12.3. Bioaccumulative potential

cyclohexane - CAS: 110-82-7

Partition coefficient: n-octano/water 3.44 - Notes: 25°C (hansch C, Leo A and Hoekman D, 1995)

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

Additional disposal information:

The product wastes have to be considered as special ones, and not dangerous ones. Their disposal must be carried out by an authorized Company, complying with local and national regulations.

Product/package (contaminated) waste: it must be submitted to a special treatment, according to the current local, national and/or European legislation.

SECTION 14: Transport information

14.1. UN number or ID number

Not classified as dangerous in the meaning of transport regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

N.A.

14.6. Special precautions for user

N.A.

14.7. Maritime transport in bulk according to IMO instruments

N.A.



Safety Data Sheet

Adhesive mixture for Ecotrap and Refill Board

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) n. 2020/878
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
Regulation (EU) n. 2018/669 (ATP 11 CLP)
Regulation (EU) n. 2018/1480 (ATP 13 CLP)
Regulation (EU) n. 2019/521 (ATP 12 CLP)
Regulation (EU) n. 2020/217 (ATP 14 CLP)
Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP)
Regulation (EU) n. 2021/849 (ATP 17 CLP)
Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 40

Restrictions related to the substances contained:

Restriction 57

Restriction 75

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

None

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.



Safety Data Sheet

Adhesive mixture for Ecotrap and Refill Board

H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1

This safety data sheet has been completely updated in compliance to Regulation 2020/878.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE: Acute Toxicity Estimate
ATEmix: Acute toxicity Estimate (Mixtures)
CAS: Chemical Abstracts Service (division of the American Chemical Society).
CLP: Classification, Labeling, Packaging.
DNEL: Derived No Effect Level.
EINECS: European Inventory of Existing Commercial Chemical Substances.
GefStoffVO: Ordinance on Hazardous Substances, Germany.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
PNEC: Predicted No Effect Concentration.
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.



Safety Data Sheet

Adhesive mixture for Ecotrap and Refill Board

STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.

1. Short title of Exposure Scenario 3: Formulation & (re)packing of substances and mixtures

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU 10: Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)</p> <p>PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation</p> <p>PROC15: Use as laboratory reagent</p>
Environmental Release Categories	ERC2: Formulation of preparations
Activity	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

2.1 Contributing scenario controlling environmental exposure for: ERC2

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
Amount used	Fraction of EU tonnage used in region:	17142 ton(s)/year
	Regional use tonnage (tons/year):	1714 ton(s)/year
	Annual amount per site	1714 ton(s)/year
	Fraction of regional tonnage used locally:	1
Frequency and duration of use	Continuous exposure	300 days/year
Environment factors not influenced by risk management	Other data. Other information	Local freshwater dilution factor:: 10
	Other data. Other information	Local marine water dilution factor:: 100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	0,025
	Emission or Release Factor: Water	2 .10 ⁻⁴

PA100476_001

20/127

EN



	Emission or Release Factor: Soil	1 .10-4
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Water	If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal., Prevent discharge of undissolved substance to or recover from onsite wastewater. (Degradation effectiveness: 96,6 %)
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to sewage treatment plant	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Degradation efficiency	96,6 %
	Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.
Conditions and measures related to external treatment of waste for disposal	Disposal methods	Prevent environmental discharge consistent with regulatory requirements.
Conditions and measures related to external recovery of waste	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	> 100 hPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Other operational conditions affecting workers exposure	Assumes use at not more than 20 °C above ambient temperature, unless stated differently.	
Technical conditions and measures to control dispersion from source towards the worker	Mixing operations (open systems) with potential for aerosol generation	Provide extract ventilation to points where emissions occur.(PROC4, PROC5)
	Transfer from/pouring from containers	Provide extract ventilation to points where emissions occur.(PROC8a, PROC8b, PROC9)
	Production of preparations or articles by tableting, compression, extrusion, pelletisation	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).(PROC14)
	Drum and small package filling	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).(PROC9)
	Equipment cleaning and	Drain down and flush system prior to equipment
PA100476_001	21/127	EN



3. Exposure estimation and reference to its source

Environment

Used EUSES model. ESVOC spERC 2.2.v1 has been used to evaluate the exposure for the environment. When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterisation ratios are expected to be less than 1.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted DNELs and the resulting risk characterisation ratios are expected to be less than 1.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.
Ensure the ventilation system is regularly maintained and tested.