

## TECHNICAL DATA SHEET

**1. TRADE NAME: UV LAMP ARACNO COMMERCIAL 30, WHITE VERSION; UV LAMP ARACNO COMMERCIAL 30, WHITE AND SHATTER VERSION**

Monitoring device to be used together with a glue board to detect the presence of flying insects like flies, gnats, wasps, bugs, noctuids, moths, anobiidi, etc.

Monitoring device for the IPM application complying with UNI EN 16636:2015 Regulation, that must be applied to control regularly the pests' presence in a specific place for a defined time.

**2. PRODUCT CODE: P-06112 (with standard tube) and P-06112SP (with shatter proof tube).**

**3. PICTURE:**



**4. TECHNICAL SPECIFICATIONS:**

**It is composed of:**

*Lamp:*

- White enamelled iron chassis;
- Power supply: 220-230 V/50 Hz;
- Protection IP degree: IP21

*Glue board:*

- Single face glue board- code: P-G06199FNC (adhesive capacity ensured for at least 60 days, despite its exposition to UV rays).
- Printed grid with numbers and letters, to facilitate the monitoring operations. The board included in the lamp is black with white grid.

*UV Tube:*

- Fluorescent tubes: n.2 standard tubes, BL 368 nm, 15W (P-06011N or P-06011F), or n.2 shatterproof tubes, BL368 nm, 15W (P-06011SPIN).

## TECHNICAL DATA SHEET

### Lamp dimensions:

- Length: 470 mm
- Width: 95 mm
- Height: 290 mm

### Glue board dimensions:

- Length: 460 mm
- Height: 299 mm

### Protection degree: IP21.

Aracno Commercial 30 is a EC certified UV lamp, which is able to catch silently the pests on the glue board.

**Colour:** As in the picture

InPEST products could undergo necessary or opportune technical changes, at any given time, without prior written notice to customers.

## 5. HOW TO USE:

Place Aracno Commercial (both versions) in the following places:

- Inside food industries, storehouses, kitchens, restaurants, pubs, and all those places where food is processed and stocked, or where the presence of flying insects is not appreciated;
- At a maximum of 2 mts height;
- On the wall;
- The glued board allows the insects catch without fragmentation, avoiding the contamination risk of the processed product.

**Theoretical covered area:** 75 m<sup>2</sup>.

**Suggested monitoring period:** all the year long.

**Suggested frequency of the controls:** 1 time every 7 days in spring-summer, 1 time every 15 days in autumn-winter.

**Glue board change:** Every month or every 15 days, according both to the pest infestation and to the season.

**UV Tubes change:** Once a year.

**Suggested maintenance:** at least 3 times per year (dust and webs removal).

## TECHNICAL DATA SHEET

Its use in very dusty places could reduce the product functionality during the time.

**Storage conditions:** in a cool and dry room, temperature below 25°C and R.H. below 55%.

### 6. PACKAGING AND SPARE PARTS:

*Package:*

- Case: 1 piece (sales unit);
- Pallet: 36 cases/pallet; pallet : 80x120x170 (h)

*Spare parts :*

- Black single face glue board (P -G06199FNC), packs of 6 pcs, case of 25 packs (150 pcs).
- Standard fluorescent tubes, BL 368 nm, 15 W, (P-06011N or P-06011F), packs of 25 pcs.
- Shatterproof fluorescent tubes, BL 368 nm, 15 W, (P-06011SPIN), packs of 25 pcs.

### 7. DISPOSAL CONSIDERATIONS:

Waste disposal should be in accordance with existing Community, National and local regulations.